

## TECHNICAL CHARACTERISTICS

### wineo silentRIGID PU underlay mat for rigid design floor for clicking in

# wineo

<b>Product thickness</b>	1.20 mm	(± 0.15 mm)	
<b>Format</b>	Length: 9 m	(± 15.00 mm)	
	Width: 1 m	(± 1.00 mm)	
<b>Weight</b>	1.5 kg/m <sup>2</sup>	(± 0.15 kg/m <sup>2</sup> )	
<b>Roll / m<sup>2</sup></b>	1 / 9 m <sup>2</sup>		
<b>Rolls / m<sup>2</sup> per pallet</b>	54 / 486 m <sup>2</sup>		

Technical details				
RWS	Reflected walking sound	13 %	(± 2 %)	Windmüller factory rating, int. (form. EPLF WD 021029-5) Measured under: SPC (EU) 5 mm without underlay
IS	Impact sound	up to 16 dB; 11 dB	(± 2 dB)	DIN EN 16251-1 Measured under: norm laminate 7 mm; SPC (EU) 5 mm
R	Thermal resistance	0.01 m <sup>2</sup> K/W		DIN CEN/TS 16354 (suit. for water underfloor heatings)
S <sub>0</sub>	Water vapor diffusion	n.a.		DIN CEN/TS 16354
RI	Residual indentation	< 0.06 mm		DIN EN 24343-1 Measured under: SPC (EU) 5 mm
CS	Compressive strength	> 55 t/m <sup>2</sup>	(> 550 kPa)	acc. to DIN EN 826 (250 Pa, 0.5 mm)
CC	Compressive creep	> 100 kPa		DIN CEN/TS 16354
DL	Dynamic load	> 3,000,000 cycles		DIN CEN/TS 16354
RLB	Resistance to large ball	~ 550 mm		DIN CEN/TS 16354 Measured under: norm laminate EPLF, 7 mm
PC	Punctual conformability	~ 0.22 mm		DIN CEN/TS 16354
RTF	Reaction to fire	Bfl-s1		DIN EN 13501-1 ( <b>excluding covering</b> )

Product description	The patented "silentRIGID" acoustic system was designed specifically for floating installation under clickable rigid-design floors (e.g. SPC or ABA). As a high-class system for reducing impact sound and walking noise, "silentRIGID" consists of up to 90% naturally occurring raw materials and is supplied in rolls for convenience.
Product composition	"silentRIGID" is composed of a transparent PET film, an ageing resistant heavy layer of polyurethane as well as a high-class fleece backside.
Taking responsibility	wineo silentRIGID is FREE from plasticizers, asbestos, formaldehyde, halogens and heavy metals and fulfils VOC Directive afset A+, Bl. Engel as well as the guidelines of the AgBB scheme.
Ecological aspects	The product is solvent-free and does not contain any other ozone-depleting substances. The renewable resources used in the product do not compete with food crops (during growth).
Health and safety	The product does not require any special health and safety measures to be taken. When laying flooring, it is <u>essential</u> to adhere to the manufacturer's advice on protection.
Processing	The approval of the flooring manufacturer <u>must</u> be obtained prior to install the product in any way. For further information about processing, please refer to the relevant <a href="#">manufacturer guidelines on installation</a> .
Installation reference	Easy cutting using an cutter knife. Lay the fleece side down and the transparent foil side up towards the surface covering. The final product installation must be checked and approved for any flooring system individually. The installation guidelines must be declared by the respective distributor.  The use of low-emission building products is recommended - e. g. products bearing the Blue Angel. This product can be recycled in accordance with EAK-no 170604 and may be disposed of as household waste.



[www.blauer-engel.de/uz156](http://www.blauer-engel.de/uz156)



emissionsgeprüft  
schadstoffgeprüft  
PREMIUM



#### Note:

The information above is based on current knowledge and the latest technical developments. We make no claim as to the completeness of information. Windmüller GmbH reserves the right to make technical changes.