























# TECHNICAL CHARACTERISTICS

wineo 800			Covering type according to EN ISO 10582: Heterogeneous resilient-flooring for glueless installation	wineo
	wineo 800 wood	wineo 800 wood XL	wineo 800 stone XL	
<b>Format</b>	1212 x 185 mm	1505 x 237 mm	914 x 480 mm	
<b>Product thickness</b>	5 mm	5 mm	5 mm	
<b>Planks, tiles / m<sup>2</sup> per box</b>	8 / 1.79 m <sup>2</sup>	6 / 2.14 m <sup>2</sup>	6 / 2.63 m <sup>2</sup>	
<b>Boxes / m<sup>2</sup> per pallet</b>	64 / 114.75 m <sup>2</sup>	56 / 119.84 m <sup>2</sup>	44 / 115.72 m <sup>2</sup>	
<b>Guarantee</b>	25 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de			
<b>Classification</b>				<b>Product composition</b>
	<b>Utilization class 23</b> Heavy-duty use in the domestic area EN ISO 10874	Corridors, living rooms, kitchens, home offices		1 <b>Surface sealing</b>
	<b>Utilization class 33</b> Heavy-duty use in the commercial sector EN ISO 10874	Department stores, lobby's, schools, open plan offices, corridors		2 <b>Surface texture</b> Various embossings
	<b>Utilization class 42</b> Normal use in the light industrial sector EN ISO 10874	Storage rooms, workshops		3 <b>Wear layer</b> Thickness 0.55 mm
	Wear resistance corresponding to the binder content – EN ISO 10582	Type I		4 <b>Decor</b> Decor film
	Wear resistance EN 660-2	Group T		5 <b>Base layer with glass fibre reinforced</b>
	Reaction to fire EN 13501-1	B <sub>fl</sub> - s1		6 <b>Profile connection</b> Connect Technology 
	Anti slip category DIN 51130	R 9		7 <b>Backing</b>
	Slip resistance EN 13893	$\mu \geq 0.30$ – DS		<b>Insulation mat silentCOMFORT</b> (separately available)
	Anti-static properties EN 1815	$\leq 2$ kV		stone - real joint technology selected decors
	Staining and chemical resistance EN ISO 26987	Good resistance according to the concentration and residence time		<b>Certifications</b>
	Light fastness EN ISO 105-B02	$\geq 6$		   
	Residual indentation EN ISO 24343-1	~ 0.07 mm		
	Castor chair test EN 425 / ISO 4918	Type W – no visible change		
	Thermal resistance EN 12667	~ 0.033 (m <sup>2</sup> K)/W ~ 0.0254 (m <sup>2</sup> K)/W in combination with silentCOMFORT		
	Impact sound reduction EN ISO 16251-1	~ 7 dB up to 14 dB in combination with silentCOMFORT		
	Dimension stability EN ISO 23999	~ 0.1 %		
	Disposal	<u>Private:</u> Possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203		

### Relevant information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by windmüller flooring products WFP GmbH.